



FOR	SEPARATE TYPE LEVEL SWITCH	
MOUNTING	TOP & SIDE, SCREW	
ENCLOSURE	WEATHER PROOF (IP65)	
FLUID NAME		Sp.Gr.
AMBIENT TEMP.	-20 ~ +60 °C	
MAX. PRESSURE	10	kgf/cm ²
MAX. TEMP	250	°C

PROCESS CONN. SIZE	PT 3/4"(M)
--------------------	------------

TAG. NO.	QT'Y	REMARK
	1	

CABLE CONNECTION SIZE	SHELL 14S
-----------------------	-----------

NO.	DESCRIPTION	MATERIAL	REMARK
1	WEIGHT	C.S	
2	BODY	C.S	
3	COVER	C.S	
4	PROCESS CONN.	304 SS	
5	SENSING ROD	316L SS	

NOTE

1. GENERAL TOLERANCE ±3mm EXCEPT AS NOTED.

△	.	.			
△	.	.			
△	.	.			
△	.	.			
△	JAN.2017	1st ISSUE	J H CHOI	D Y KIM	B S SUNG
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY



HITROL CO., LTD.

TITLE

VIBRATION TYPE LEVEL SWITCH
HTM-930

SCALE	UNIT	SHEET NO.
N.S	mm	—

PROJECT
DRAWING NO.
HTM930-A-01

This drawing is the property of HITROL and shall not be copied, communicated, or given for third-party except with our written permission