



Caratteristiche a 6.3 bar

Velocità a Vuoto	600	rpm
Coppia di Spunto	8.8	Nm
Coppia Potenza Max	5.3	Nm
Consumo Aria	5,3	l/s
Potenza	200	W

MODIFICHE							 Italy																			
REVIS.	N.	DESCRIZIONE MODIFICA																								
DATA	24/08/2007	MATERIALE	FIAM	TOLLERANZE GENERALI UNI EN 22768-1					TOLLERANZE	SCALA	1:1															
FIRMA	PADOVAN		UNI	<table border="1"> <tr> <td>0.5<6</td> <td>6<30</td> <td>30<120</td> <td>120<400</td> <td>>400</td> </tr> <tr> <td>±0.05</td> <td>±0.10</td> <td>±0.15</td> <td>±0.20</td> <td>±0.30</td> </tr> </table>	0.5<6	6<30	30<120	120<400	>400			±0.05	±0.10	±0.15	±0.20	±0.30	<table border="1"> <tr> <td><10</td> <td>10<50</td> <td>50<120</td> <td>120<400</td> <td>>400</td> </tr> <tr> <td>±1°</td> <td>±30'</td> <td>±20'</td> <td>±10'</td> <td>±5'</td> </tr> </table>	<10	10<50	50<120	120<400	>400	±1°	±30'	±20'	±10'
0.5<6	6<30	30<120	120<400	>400																						
±0.05	±0.10	±0.15	±0.20	±0.30																						
<10	10<50	50<120	120<400	>400																						
±1°	±30'	±20'	±10'	±5'																						
UISTO		TRATT.		A TERMINI DI LEGGE CI RISERVIAMO LA PROPRIETA' DEL PRESENTE DISEGNO CON DIVIETO DI RIPRODUZIONE TOTALE O PARZIALE					<table border="1"> <tr> <td>6g</td> <td>6H</td> </tr> </table>	6g	6H															
6g	6H																									
DENOM.	MOTORE PNEUMATICO 20M60D-SAL-M12					COD.	183309018		REV.	0																