


Dimensions	PU Pieces	€/100/Mat.
Article	88424.700	RAZ 4950
88424	Aluminium	S




**Blind rivet nuts, round, open-end,
S = countersunk head 90°**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 4/1,5 -3,5	S 500	14,10
M 5/1,5 -4,0	S 500	16,00
M 5/3,5 -6,0	S 500	17,00
M 6/1,5 -4,5	S 250	25,50
M 6/4,0 -6,5	S 250	27,00
M 8/1,5 -4,5	S 100	33,00
M 8/4,0 -6,5	S 100	33,50
M 10/1,5 -4,5	S 100	47,00
M 10/4,0 -6,5	S 100	48,00

Article	88424.920	RAZ 4950
88424	A 2 (1.4567)	S




**Blind rivet nuts, round, open-end,
S = countersunk head 90°**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 4/1,5 -3,0	S 500	94,00
M 4/2,5 -4,0	S 500	96,00
M 5/1,5 -4,0	S 500	101,00
M 5/3,5 -6,0	S 500	104,00
M 6/1,5 -4,5	S 250	155,00
M 6/4,0 -6,0	S 250	160,00
M 8/1,5 -4,5	S 100	207,00
M 8/4,0 -6,0	S 100	212,00

Article	88424.940	RAZ 4950
88424	A 4	S




**Blind rivet nuts, round, open-end,
S = countersunk head 90°**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 4/1,5 -3,0	S 500	30,00
M 4/2,5 -4,0	S 500	30,50
M 5/1,5 -4,0	S 500	32,50
M 5/3,5 -6,0	S 500	34,00
M 6/1,5 -4,5	S 250	41,00
M 6/4,0 -6,0	S 250	41,50
M 8/1,5 -4,5	S 100	59,00
M 8/4,0 -6,0	S 100	60,00

Dimensions	PU Pieces	€/100/Mat.
Article	88480.010	RAZ 4950
88480	Steel zinc plated	F




**Blind rivet nuts, round, closed-end,
for air- and water-tight rivetting,
F = protruding head**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 5/0,5 -3,0	S 500	31,00
M 5/3,0 -5,5	S 500	34,00
M 6/0,5 -3,0	S 500	41,00
M 6/2,5 -5,5	S 500	43,00
M 8/0,5 -3,5	S 200	57,00
M 8/3,0 -6,0	S 200	62,00
M 10/1,0 -3,0	S 250	71,00

Article	88480.700	RAZ 4950
88480	Aluminium	F




**Blind rivet nuts, round, closed,
for air- and water-tight rivetting,
F = protruding head**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 5/0,3 -3,0	S 500	16,00
M 5/3,0 -4,0	S 500	17,50
M 6/0,5 -3,0	S 500	26,00
M 6/3,0 -4,5	S 500	27,50
M 8/0,3 -3,0	S 250	36,00
M 8/3,0 -5,5	S 250	38,00

Article	88481.010	RAZ 4950
88481	Steel zinc plated	S




**Blind rivet nuts, closed-end,
for air- and water-tight rivetting,
S = countersunk head 90°**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 4/1,5 -3,5	S 500	29,00
M 5/1,5 -4,0	S 500	33,00
M 6/1,5 -4,5	S 500	43,00
M 6/4,5 -6,0	S 500	43,50
M 8/1,5 -4,5	S 250	60,00
M 8/4,5 -6,0	S 250	62,00

Dimensions	PU Pieces	€/100/Mat.
Article	88481.700	RAZ 4950
88481	Aluminium	S




**Blind rivet nuts, closed-end,
for air- and water-tight rivetting,
S = countersunk head 90°**

Dimensions → **TI-207**

Internal thread M/min.-max. clamping range

M 5/1,5 -4,0	S 500	18,50
M 6/1,5 -4,5	S 500	26,00
M 8/1,5 -4,5	S 500	37,50

Article	88490.010	RAZ 4950
88490	Steel zinc plated	MG-F




**Blind rivet nuts, round, open-end,
MG = with multigrip rivet body
F = protruding head**

Dimensions → **TI-206**

Internal thread M/min.-max. clamping range

M 4/0,5 -6,0	S 500	19,60
M 5/0,5 -6,0	S 500	23,20
M 6/0,5 -6,0	S 500	31,50
M 8/0,5 -7,5	S 500	41,50

Article	88490.700	RAZ 4950
88490	Al-alloy	MG-F



**Blind rivet nuts, round, open-end,
MG = with multigrip rivet body
F = protruding head**

Dimensions → **TI-206**

Internal thread M/min.-max. clamping range

M 4/0,5 -6,0	S 500	11,40
M 5/0,5 -6,0	S 500	13,20
M 6/0,5 -6,0	S 500	20,40
M 8/0,5 -7,5	S 500	26,00