

Revision Number: 002.2

Issue date: 11/10/2014

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

BONDERITE L-GP 39SY201(310 PENT)

GEAR MARKING COMPOUND known

as 39SY201(310 PENT)

Product type: Restriction of Use: Special product

None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number:

595899

Item number:

595899

Region:

**United States** 

**Contact information:** Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY	
SKIN IRRITATION	2	
EYE IRRITATION	2A	
ASPIRATION HAZARD	1	



#### **Precautionary Statements**

Prevention:

Response:

Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves. IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash

with plenty of soap and water, IF IN EYES: Rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to remove. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage:

Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 595899

Product name: BONDERITE L-GP 39SY201(310 PENT) GEAR MARKING COMPOUND known as 39SY201(310 PENT)

Hazardous Component(s)	CAS Number	Percentage*	
Lubricating grease	Proprietary	30 - 60	
Iron hydroxide oxide yellow	51274-00-1	30 - 60	
Petroleum Distillates	Proprietary	10 - 30	
Alkylphenol ethoxylate	Proprietary	1 - 5	

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). If

symptoms develop and persist, get medical attention. If this material is injected beneath the skin, regardless of amount injected, get immediate

medical attention. Do not wait for symptoms to develop.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

Ingestion: Get medical attention. DO NOT induce vomiting unless directed to do so by

medical personnel.

Symptoms: See Section 11.

Notes to physician: This material, if aspirated into the lungs, may cause chemical pneumonitis;

treat the affected person appropriately.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: This product is combustible at high temperatures.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear suitable protective

clothing, gloves and eye/face protection. Eliminate ignition sources including

sources of electrical, static or frictional sparks.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

### 7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Do not take internally. For industrial use only. Provide adequate

ventilation.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Lubricating grease	None	None	None	None
Iron hydroxide oxide yellow	5 mg/m3 TWA Iron oxide fume as Fe 5 mg/m3 TWA mist 5 mg/m3 TWA mist 10 mg/m3 STEL mist 10 mg/m3 STEL Iron oxide fume as Fe 5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.		None	None
Petroleum Distillates			tes 5 mg/m3 TWA mist 500 ppm (2,000 None 10 mg/m3 STEL mist mg/m3) PEL	None
lkylphenol ethoxylate None None		None	None	

**Engineering controls:** 

Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection:

Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Odor: **Odor threshold:** 

Vapor pressure:

Boiling point/range: Melting point/ range:

Specific gravity:

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper: Autoignition temperature:

**Evaporation rate:** Solubility in water: Partition coefficient (n-octanol/water):

**VOC** content: Viscosity: Decomposition temperature: Paste Yellow

Petroleum Not available.

Not applicable Not determined

> 300 °F (> 148.9 °C) calculated

Not determined

0.900 at 16 °C (60.8 °F)

Not determined

149 °C (300.2 °F) calculated

Not determined Not determined

Not determined Not determined Negligible

Not determined 7.5 lb/gal Not available.

Not available.

### 10. STABILITY AND REACTIVITY

Stability:

Stable at normal conditions.

Hazardous reactions:

Will not occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

Incompatible materials:

Not available.

Reactivity:

This product may react with strong acids, bases and oxidizing agents.

Conditions to avoid:

Avoid excessive heat and ignition sources.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

Inhalation:

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Excessive inhalation of this material causes headache, dizziness, nausea and incoordination. Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil

granuloma formation, inflammation and increased incidence of infection.

Skin contact:

Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis. If this

material is injected beneath the skin, regardless of amount injected, get immediate medical

attention. Do not wait for symptoms to develop.

Eye contact:

This product may be severely irritating to the eyes.

Ingestion:

Ingestion of this product may cause nausea, vomiting and diarrhea. May cause dizziness. incoordination, headache, nausea, and vomiting. Small amounts of this product, if aspirated

into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Lubricating grease	None	No Data	
ron hydroxide oxide yellow	None	Irritant	
Petroleum Distillates	None	Irritant	
Alkylphenol ethoxylate	None	Irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Lubricating grease	No	No	No
Iron hydroxide oxide yellow	No	No	No
Petroleum Distillates	No	No	No
Alkylphenol ethoxylate	No	No	No

### 12. ECOLOGICAL INFORMATION

**Ecological information:** 

IDH number: 595899

No data available.

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

Packing group:

None None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None

Packing group:

None None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number: Packing group:

None None

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification:

CERCLA/SARA Section 302 EHS:

None above reporting de minimis

CERCLA/SARA Section 311/312:

Immediate Health

**CERCLA/SARA Section 313:** 

None above reporting de minimis

None above reporting de minimis

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

**CEPA DSL/NDSL Status:** 

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by:

Jennifer Mckay, Regulatory Affairs Specialist

Issue date:

11/10/2014

IDH number: 595899

Product name: BONDERITE L-GP 39SY201(310 PENT) GEAR MARKING COMPOUND known as 39SY201(310 PENT)

Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 595899 Product name: BONDERITE L-GP 39SY201(310 PENT) GEAR MARKING COMPOUND known as 39SY201(310 PENT)